



Antialga

RESERVOIRS FREE OF ALGAE AND CONTAMINATION

ANTI-ALGAE FOR GREENHOUSES

COMPOSITION

Mixture of quaternaries
Sequestrants
Quaternary ammonium salts
Synergizing
Demineralised water

C.P CHARACTERISTICS

pH 6.0-9.0 +/- 0.5
Density 0.95 +/- 0.5
Color Colourless
Smell Slight
Solubility Completed

FORMULATION

Liquid

CLASSIFICATION

Danger



PACKAGING

Tank 10 L
Tank 20 L



Made in Italy



ANTIALGA is a concentrated, extremely active product that can break down and prevent the formation of algae.

These organisms accumulate slowly, sometimes creating difficult problems, soiling the crops and depriving them of their nourishment, clogging the irrigation lines and accumulating in the collection basins. They can also be a place of pathogen proliferation.

ANTIALGA is essential for the restoration and cleaning of structures. It frees the

surfaces from the presence of algae, making the environment healthier for crops, avoiding the spread of infections and diseases. The product is not dangerous to operators and crops. It does not corrode media and does not gasify.

ANTIALGA can be used for the removal of algae from pallets, sheets, troughs, equipment, tanks, pots. Excellent in flow/reflux tanks and sub-flooding sheets, as well as for the maintenance of cooling systems.

DOSES AND METHODS OF USE

- For the removal of algae from all surfaces in the absence of plants: apply **ANTIALGA** diluted 2-4% with water and distribute well wetting the affected surfaces.
- For the removal of algae from "flow and reflux" tanks and sheets for subirrigation in the presence of plants: add **ANTIALGA** in relation to 60-80 ml/m³ of irrigation solution. Repeat the addition as necessary.

WARNINGS: In case of abundant presence of algae, it is advisable to mix with **STERIL®** at the same dosage.